



STANDARD FEATURES

- Large stainless steel weighing surface
- Large 0.6 in (15.24 mm) high contrast Liquid Crystal Display (LCD)
- Integral security bracket
- Underweigh function (includes hook)
- Sealed front panel and molded spill ring
- Stability indicator
- Overload and underload indicators
- Auto shut-off (user enabled/disabled)
- Low-battery indicator
- Battery or AC operation (AC adapter included)
- Span calibration mass (included on SP202, SP402, SP401, SP601 models)
- Integral shipping lock
- Parameter lock switch

SPECIFICATIONS

	SP202	SP402	SP602	SP401	SP601
Part#	77654	77655	103099	77656	77657
List Price	Consult	Consult	Consult	Consult	Consult
Capacity	200 g	400 g	600 g	400 g	600 g
Resolution	0.01 g	0.01 g	0.01 g	0.1 g	0.1 g
Operating Modes	Parts Counting with Average Piece Weigh Recalculation, Percentage Weighing, Totalization, Display Hold				
Repeatability	0.01 g			0.1 g	
Linearity	±0.01		±0.02		±0.1
Stabilization Time	3 seconds				
Operating Temperature	50°F to 104°F (10°C to 40°C)				
Pan size	Ø 4.7 in (12 cm)				6.5 x 5.5 in (16.5 x 14.2 cm)
Dimensions	7.56 x 2.13 x 8.27 in (19.2 x 5.4 x 21.0 cm)				
Weight (Approx.)	1.5 lb (0.7 kt)		1.8 lb (0.8 kg)		
Est. Ship Weight	4 lb (1.8 kg)				
Calibration Weight	200 g	400 g	600 g	400 g	600 g
Power	120V AC Adapter (included) or 4 "AA" Batteries (not included)				
Warranty	Two-year limited warranty				
Return Policy	Ohaus Standard Policy - restock fee may apply				
Ounces	7.0550 x 0.0005 oz	14.1095 x 0.0005 oz	21.645 x 0.0005 oz	14.110 x 0.0005 oz	21.165 x 0.0005 oz
Pounds	-	-	1.32280 x 0.00005 lb	-	1.3230 x 0.00005 lb
Pound, Ounce	-	-	1 lb:5.165 oz x 0.001 oz	-	1 lb:5.165 oz x 0.01 oz
Troy ounces	6.4300 x 0.0005 ozt	12.8605 x 0.0005 ozt	19.2905 x 0.0005 ozt	12.860 x 0.0005 ozt	19.290 x 0.0005 ozt
Pennyweight	128.60 x 0.01 dwt	257.21 x 0.01 dwt	385.81 x 0.01 dwt	257.2 x 0.1 dwt	385.8 x 0.1 dwt

SPECIFICATIONS

	SP2001	SP4001	SP6001	SP6000	
Part#	77658	77660	103100	77661	
List Price	Consult	Consult	Consult	Consult	
Capacity	2000 g	4000 g	6000 g	6000 g	
Resolution	0.1 g	0.1 g	0.1 g	1 g	
Operating Modes	Parts Counting with Average Piece Weigh Recalculation, Percentage Weighing, Totalization, Display Hold				
Repeatability	0.1 g			1 g	
Linearity	±0.1		±0.2	±0.1	
Stabilization Time	3 seconds				
Operating Temperature	50°F to 104°F (10°C to 40°C)				
Pan size	6.5 x 5.5 in (16.5 x 14.2 cm)				
Dimensions	7.56 x 2.13 x 8.27 in (19.2 x 5.4 x 21.0 cm)				
Weight (Approx.)	1.8 lb (0.8 kg)				
Est. Ship Weight	4 lb (1.8 kg)				
Calibration Weight	2000 g	4000 g	6000 g	6000 g	
Power	120V AC Adapter (included) or 4 AA Batteries (not included)				
Warranty	Two-year limited warranty				
Return Policy	Ohaus Standard Policy - restock fee may apply				
UNIT OF MEASURE	Kilogram	2.0000 x 0.0001 kg	4.0000 x 0.0001 kg	6.0000 x 0.0001 kg	6.000 x 0.001 kg
	Ounces	70.550 x 0.005 oz	141.095 x 0.005 oz	211.645 x 0.005 oz	211.65 x 0.05 oz
	Pounds	4.4090 x 0.0005 lb	8.8185 x 0.0005 lb	13.2280 x 0.0005 lb	13.230 x 0.005 lb
	Pound, Ounce	4 lb:6.550 oz x 0.01 oz	8 lb:13.095 oz x 0.01 oz	13 lb:3.65 oz x 0.01 oz	13 lb:3.65 oz x 0.05 oz
	Troy ounces	64.300 x 0.005 ozt	128.605 x 0.005 ozt	192.905 x 0.005 ozt	192.90 x 0.05 ozt
	Pennyweight	1286 x 0.1 dwt	2572.1 x 0.1 dwt	3858.1 x 0.1 dwt	3858 x 1 dwt

PART NUMBER/PRICE

PART #	MODEL #	DESCRIPTION	PRICE
77654	SP202	200 g x 0.01 g	Consult
77655	SP402	400 g x 0.01 g	Consult
103099	SP602	600 g x 0.01 g	Consult
77656	SP401	400 g x 0.1 g	Consult
77657	SP601	600 g x 0.1 g	Consult
77658	SP2001	2000 g x 0.1 g	Consult
77660	SP4001	4000 g x 0.1 g	Consult
103100	SP6001	6000 g x 0.1 g	Consult
77661	SP6000	6000 g x 1 g	Consult

OPTIONS/ACCESSORIES

PART #	MODEL #	DESCRIPTION	PRICE
70422	77256-01	Hard shell carrying case	Consult
77710	71147376	RS-232 interface with integrated cable, DB9	Consult
118780	71147377	USB interface with integrated cable	Consult
83222	12102320	115V AC adapter	Consult
35263	76288-01	Security device	Consult
67413	SW12W	WinWedge® TAL Software	Consult
104767	—	Impact printer	Consult
104770	—	Paper for PN 104767	Consult
104771	—	Ribbon for PN 104767	Consult
92804	71168909	In-use cover, set of 3	Consult
156234	46001724	220V AC power supply	Consult
156235	46001780	Plug set	Consult